



Installation Instructions and Warranty Information

2005 Jeep Liberty 3.7L



P/N 1930S

Read all instructions carefully before attempting installation.

11.27.06

Installation instructions for JBA Headers p/n 1930S 2005 Jeep Liberty 3.7L

NOTE: Installation of this product requires an adequate workspace, general mechanic's tools, general mechanical "know-how" and a reasonable degree of experience. Most auto enthusiasts with these resources will have little difficulty installing these headers. However, you should carefully read these instructions before attempting to install these headers. If in doubt, consult a professional mechanic. (Better to do it now than to get stuck halfway through the installation.) This part is certified for use on Emission Controlled Vehicles.

By installing your JBA Performance Exhaust product, you indicate that you have read this document and agree with the following terms.

The Purchaser is responsible for following all installation instructions and safety guidelines supplied with JBA Performance Exhaust products.

JBA Performance Exhaust assumes no responsibility for damages resulting from improper operation, misuse, abuse, or lack of responsible care, or any problems resulting from incompatibility with other manufacturer's products.

Included with your installation instructions is a copy of the product warranty. Please read it carefully before you begin any work on your vehicle. Should you have any questions about the warranty policy or installation, please give JBA a call at 619 229-7797.

JBA uses sealing beads on all its headers. We have found that when installed correctly the raised bead around each port increases the pressure exerted on the gasket directly adjacent to the port and effectively prevents leaking gaskets. It is important when installing the header, to install all bolts loosely, then tighten evenly to ensure the flat installation of the flange. It is normal for the flange to be raised off the cylinder head the thickness of the sealing bead.

RECOMMENDED TOOLS:

10mm socket
12mm socket
13mm socket and wrench
9/16" socket and wrench
WD-40 or equivalent penetrating oil

WARNING: The head gaskets on this vehicle are made of thin stainless steel. They are extremely sharp! Wear gloves!

1. Place vehicle in a location where the floor is solid and flat, with adequate lighting. Do not attempt to work on a hot engine. Heat causes metal to expand and makes removal of fasteners difficult at best. Disconnect the battery cables from the battery. Raise the front of the vehicle to obtain adequate access to the bottom exhaust manifold flanges. Use large-base jack stands to support the vehicle. Do not rely on the jack! Block the tires to prevent the vehicle from rolling off the jack stands.

2. Spray WD-40 or some type of penetrating oil on all accessible fasteners and fittings before attempting to remove them.
3. Unbolt the exhaust system from exhaust manifolds.
4. Unbolt the heat shields from the exhaust manifolds and remove.
5. Unbolt the exhaust manifolds and remove them.
6. Clean gasket material from the cylinder head surface. Be careful not to gouge head surface.
7. Install the new JBA headers using gaskets, and hardware provided.
8. Reconnect the exhaust system using the supplied hardware. The flange nuts are used on the forward point on the collector flanges.
9. Reconnect battery cables.
10. Start the engine and let it warm up. Check for leaks. Shut engine off and let it cool down. Check to make sure all fasteners are tight.
11. Recheck everything!
12. All tubular headers require maintenance including periodically checking and retightening of the header bolts.

Parts List:

- (1) Driver side header
- (1) Passenger side header
- (2) Head flange gaskets
- (12) 8mm bolts with lock washers
- (2) 3/8 – 16 x 2-1/2 bolts w/ nuts and lock washers
- (2) 3/8 – 16 x 2 bolts
- (2) Flange nuts
- (2) 3/8 flat washers

Other recommended parts:

Get even more performance with a stainless steel JBA performance exhaust system.

Applications Part No.

2005 Liberty 3.7L 40-1540

For more information about this and other JBA products visit www.jbaheaders.com

LIMITED LIFETIME WARRANTY

All products manufactured by JBA are guaranteed to be free from defects in materials and workmanship at the time of sale. All products are guaranteed to fit the intended application, provided the vehicle has not suffered structural damage or other modification*. Claims for damage occurring during shipment must be made to the carrier. JBA, at its option, will repair or replace any product found to be defective in materials or workmanship.

Failure of any JBA product while on the originally installed vehicle, will entitle the original purchaser to repair, replacement, or pro rata credit according to the following chart:

Up to 2 years from the date of purchase	JBA will repair or replace at its option
After 2 years	JBA will allow credit of 50% of the current price

Certain uses or occurrences listed below will void this warranty.

PURCHASER ASSUMES RESPONSIBILITY: JBA expressly disclaims, and the purchaser expressly assumes, responsibility for all labor related costs and any incidental or consequential damages arising from any JBA product installation or failure. JBA's liability is limited to the purchase price of the product. JBA, at its option, may refund the amount of the purchase to end a warranty claim. Labor charges incurred to install or remove the product are not covered. Damage resulting from incorrect timing, fuel system problems, clogged catalytic converters or backfire is not covered. Charges for the loss of use of vehicle, car rentals, and towing are the responsibility of the customer and are not covered. Cost of customer-applied coatings is not covered. As sound preference is subjective, sound is not warranted. Other than the warranty described herein, JBA products are sold "AS IS". No warranty terms are implied. The terms of this warranty are severable. Any provision voided by state or other applicable law shall not act to enlarge other provisions of this warranty except as expressly required by law. Catalytic converters and other products sold but not manufactured by JBA are subject to the product manufacturer's warranty only and are not warranted by JBA.

THE FOLLOWING WILL VOID THIS WARRANTY: Use of "heat-wrap" products and/or the use of fuels other than gasoline will void this warranty. Damage caused by improper installation is not covered under this warranty. Damage caused by collision, road hazards, or failure of other components is not covered. Any repair or alteration to a JBA product not performed by JBA or its authorized agents will void this warranty.

NO FREIGHT WARRANTY: JBA does not warrant freight. The purchaser will be responsible for freight to and from JBA. Contact JBA to make a warranty claim and to receive a return authorization number. Return the product freight prepaid **along with a copy of the original purchase invoice** and a written description of the problem including the return authorization number to the address below. JBA does not accept freight-collect shipments. A product found to be defective or otherwise covered under this warranty will be repaired or replaced per the above policy and returned freight-collect.

JBA cannot assume responsibility for compliance with local law and regulations regarding smog and noise standards. Headers described as "smog legal" are warranted to be C.A.R.B. (California Air Resources Board) exempt or pending exemption approval. This warranty is extended solely to the original purchaser and for the original vehicle on which the product was installed.

JBA reserves the right to change the design, material, or specifications of any product without notice.

Automotive Engineered Products, Inc.
dba JBA Headers and Performance Exhaust
7149 Mission Gorge Road, Suite D
San Diego, California 92120
(619) 229-7797

Copyright 2005 by Automotive Engineered Products, Inc. All rights reserved.

* Note that certain custom headers may require different engine mounts or brackets for proper fit.